6-1/2" PLUNGE CIRCULAR SAW

Model SP6000K

ADDITIONAL FEATURES & BENEFITS

- Easy to set depth adjustment with large scale
- Smooth and convenient plunge release lever for operator comfort
- Bevel capability (-1° to 48°) with positive stops at 22.5° and 45°
- Magnesium components deliver a well balanced and lightweight saw at only 9.1 lbs.
- Dual front and rear bevel supports provide additional rigidity for precise and accurate bevel cuts
- Precise bevel cutting as the position of the blade enters the material on the same cutting line whether cutting straight or bevel
- Close to the wall cutting (11/16") for expanded cutting applications
- Locking lever holds the blade in position so that the wrench can be inserted through the hole in the blade case for easier blade installation
- Blade wrench attaches to the saw for fast and convenient blade changes
- Electric brake for improved productivity
- Built-in depth stop allows a preliminary cut of 1/16" to be performed before the entire material is cut through for clean and splinter-free cutting
- Rubberized handles for added comfort
- Large 1-7/16" rear dust port directs material away from the operator and easily connects to a vacuum system
- Includes a premium 48 tooth carbide-tipped blade

FEATURES WITH OPTIONAL GUIDE RAIL

- Optional guide rail system interacts with the saw base to provide smooth perfect dead-on straight or bevel cutting
- Tool-less cam adjustments on the saw base enable fine tuning to the guide rail minimizing play for more precise cutting
- Slide lever built into the saw base locks the saw to the guide rail to help support the saw while making bevel cuts
- Saw base is attachable to other guide rail systems in the market

STANDARD EQUIPMENT

- Carbide-Tipped Blade - 48T (B-07353)
- Hex Blade Wrench (783203-8)
- Plastic Tool Case

SPECIFICATIONS

Blade diameter	6-1/2"
Arbor	13/16"
Max cutting capacities: 90°	2-3/16"
45°	1-9/16"
No load speed	2,000 - 5,200 RPM
Watts out	1,300
AMPS (120V)	12
Overall length	13-3/8"
Net weight	9.1 lbs.
Shipping weight	16.2 lbs.
UPC	088381-078443

EASY BLADE CHANGES

Locking lever holds the blade in position to be replaced

Wrench is inserted through a hole in the blade case



Blade wrench attaches to the saw for convenience



Model SP6000K

088381078443

OPTIONAL ACCESSORIES

- Guide Rail: (117") (194367-7)
  (54") (194368-5)

- Clamp Set (194385-5)

- Guide Rule (165447-6)



Cam adjustments minimize play for precise cutting

Makita offers a wide variety of CIRCULAR SAW accessories. For a complete listing, please refer to the Makita General Catalog, or visit our website at makitatools.com, or call 1-800-4MAKITA.

All specifications subject to change without prior notice. All models and accessories subject to stock on hand.

NTF-0808-400 MA-0803-08 For more information, call **1-800-4MAKITA** or visit **makitatools.com**

makita®

Makita U.S.A., 14930 Northam St., La Mirada, CA 90638